


DATASHEET

# Chicago Metallic 100 mm Bandraster 3100



## Chicago Metallic 100 mm Bandraster 3100

- The 100 mm wide grid system is suitable for the flexible layout of large spaces and positioning of partition walls
- Suitable for the installation of acoustic and fire protection barriers in plenum spaces
- System includes a wide range of spacers and accessories
- Compatible with exposed, semi-concealed and concealed grid ceilings

#### Coupling Compatible tiles **Cross-section** Semi-concealed Straight-cut Exposed Concealed 100 mm

#### **Assortment**

Product group		Component description	Height (mm)	Length (mm)	Colour	Pcs per pack	Lm per pack	Kg per pack	Carton per pallet	Kg per pallet	
Main runner											
BR100		Bandraster main runner 100 mm - without slots	35,4	3600	11, 001	8	28,8	30,9	30	928	
Cross tee											
BR100 T15 HD CT		Bandraster cross tee T15 Hook	38		11, 001						
BR100 T24 CT		Bandraster cross tee T24 Hook	38								
BR100 T24 HD CT			38								
Wall angle options											
L24x24		L-wall angle 24x24 mm colour	24	3050	Color-all, 11	40	122	25,5	60	1528	
L24×24		L-wall angle 24x24 mm white	24	3050	001	20	61	12,7	60	1528	
W10x15	** THE SOLD OF CO. KM2 *	W-profile 15x15x10x15 mm	15	3050	Color-all, 04, 88, 11, 001, 901	30	91,5	19,9	60	1191	

Contact Rockfon® for the full range of wall angles and accessories.

Please note that not all colors are available for every product. We recommend checking the assortment table for the colors currently offered for each item. If you need further assistance or have specific color preferences, please feel free to contact Rockfon.



Product group		Component description	Height (mm)	Length (mm)	Colour	Pcs per pack	Lm per pack	Kg per pack	Carton per pallet	Kg per pallet	
Accessories											
BR100 LC		Length coupling for bandraster 100 mm				25		3,5			
BR100 H		Flat hanger for bandraster 100 mm	100			100		3,4			
BR100 CC		Cross connector for bandraster 100 mm				25		2,7			
BR100 WC		Wall connector for bandraster 100 mm				25		2,7			
BR100 HB		Bent hanger for bandraster 100 mm	84,7			100		3,4			
PINC BR		Slot pincer for bandraster 50, 75, 100, 125, 150 mm				1		2,5			
NH CLIP		Intersection clip for nonius				200		1,3			
NH NAIL						200		1,3			

Contact Rockfon® for the full range of wall angles and accessories.

Please note that not all colors are available for every product. We recommend checking the assortment table for the colors currently offered for each item. If you need further assistance or have specific color preferences, please feel free to contact Rockfon.

### Performance



Reaction to fire

**Corrosion Resistance** 



**Environment** 

Fully Recyclable

# Understanding the performance of Chicago Metallic grids and accessories



#### Reaction to fire

Reaction to fire is classified in accordance with EN 13501-1. Chicago Metallic steel grids and accessories are non-combustible.



#### Fire resistance

A range of Chicago Metallic steel grids are tested in combination with different Rockfon tiles and are classified in accordance with European norm EN 13501-2 and/or national norms.



#### Colours

Chicago Metallic grids are available in various colours from the RAL and NCS systems, which are measured following the ISO 7724-2 and ISO 7724-3 standards. The actual colours may deviate slightly from the RAL and NCS references. Chicago Metallic grids are available in a variety of finishes from matt to high gloss, with a respective average of < 5, 15 and 50 units at a 60° angle. The matt finishing is measured at an angle of 85°. See the colour legend for their average values. The gloss unit is measured in accordance with EN13523 part 2.



#### Corrosion resistance

Chicago Metallic products produced from hot dip galvanised steel following the Sendzimir process comply with the corrosion classes of the product standard EN 13964 (A, B, C, D). The standard systems in class B are protected with 100 g/m² zinc evenly applied on both sides. The enhanced corrosion resistance (ECR) systems and accessories in class C or D have respectively a layer of 100 g/m² and 275 g/m² zinc evenly applied on both sides and are protected with an additional layer of 20 micron paint per side.



#### Load bearing performance

The load bearing performance (max. kg/m² load applicable to the grid system without exceeding the allowable deflection of the individual components) is tested in accordance with the EN 13964 standard. The accumulative value of the system deflection, shown on the data sheets, does not exceed the max. deflection as given in class 1 of the standard. Special project configurations deviating from the standard module sizes mentioned in the data sheets must be calculated by Rockfon technical services.



#### Cleaning

All Chicago Metallic grids can be cleaned with water and a mild detergent in combination with a melamine foam sponge or microfiber cloth.

## Colour legend

Please note that not all colors are available for every product. We recommend checking the assortment table for the colors currently offered for each item. If you need further assistance or have specific color preferences, please feel free to contact Rockfon.

White 001

White 901

White 01 White 916 Matt White 11

L value: 93 Gloss: 2 at both a 60° and 85° angle

Platinum 54

Alugrey 04

Galvanised 00 Galvanised 69 Matt Black 88 RAL 9004

Gloss: 4.5 at 60° angle and 11.5 at 85° angle

Brushed Alu 534

High Gloss Chrome 14 Carrara 57

High Gloss Brass 16

White 001 / White 001 (8WW) RAL 9003 / RAL 9003

Black 08 / Black 08 (8BB) RAL 9005 / RAL 9005

White 001 / Black 08 (8WB) RAL 9003 / RAL 9005 Alugrey 04 / Black 08 (8GB) RAL 9006 / RAL 9005

## Rockfon Color-all®



<sup>\*</sup> Colour contains effect pigments.

Please note that not all colors are available for every product. We recommend checking the assortment table for the colors currently offered for each item. If you need further assistance or have specific color preferences, please feel free to contact Rockfon.

NCS codes are closest colour match. The actual colour of the Rockfon Color-all® grid may deviate slightly from printed colours due to the texture of the surface. Samples are available upon request.

<sup>\*\*</sup> Colour is between NCS S 5030-R90B and NCS S 6030-R90B.

## **Sounds Beautiful**

