

Rockfon® Soundstop



Rockfon® Soundstop

- Acoustic barriers which reduce noise transfer in ceiling and floor plenums
- Easy to install above or below modular partitions

Product Description

- Stone wool panel with aluminium foil membrane
- 30 dB rating requires two layers of panels, each 30mm thick, placed back to back

Application Areas

- Office
- Healthcare
- Education
- Industry
- Leisure
- Retail

	Module size (mm)	Weight (kg/m ²)	A1-A3 Production stage impact (kg CO ₂ eq/m ²)*	A1-C4 Full life cycle impact (kg CO ₂ eq/m ²)*
Soundstop 21 dB	1200 x 1000 x 65	4.7	5.83	7.14
Soundstop 30 dB	1200 x 1000 x 60	6.9	7.85	9.74

Soundstop 30 dB: The actual thickness equals 2x30 mm

* For full environmental impact disclosure, see our product EPDs available on [rockfon.link/cee-epd](#). Due to differences in calculation methods and scenario assumptions, environmental impact values are generally not directly comparable between manufacturers.



Performance



Direct sound insulation

$R_w = 21$ dB

$R_w = 30$ dB



Room to room sound insulation

-

*) Values obtained on the basis of theoretical analysis.

Product	$D_{n,f,w}$	$D_{n,f,w}$ with Rockfon Soundstop 21 dB	$D_{n,f,w}$ with Rockfon Soundstop 30 dB
Rockfon Blanka A (20mm)	26		
Rockfon Blanka D/Aex (20mm)	25		
Rockfon Blanka dB 35	35	44*	50*
Rockfon Blanka dB 41	41	50*	55*
Rockfon Blanka dB 43	43	53*	56*
Rockfon Blanka dB 46	46	55*	58*
Rockfon Sonar dB 35	35	44*	50*
Rockfon Sonar dB 41	41	51*	55*
Rockfon Sonar dB 43	43	52*	56*
Rockfon Sonar dB 46	46	55*	58*



Reaction to fire

A1



Humidity and sag resistance

Up to 100% RH



Hygiene

Stone wool provides no sustenance to microorganisms



Recyclability

Fully recyclable stone wool



Indoor environment

Rockfon ceiling products are classified in Class E1 in accordance with EN 13964 (EN 717-1). Rockfon ceiling products have a very low release of VOCs. A selection of Rockfon products have achieved the following performance levels and labels in indoor air emissions:



Material Health

All materials used in Rockfon products are screened against the list of substances restricted under REACH or recognized as Substances of Very High Concern (SVHC) on an ongoing basis. Rockfon stone wool fibres comply with the safe fibre EU regulation and hold an EUCEB certification.

Rockfon production facilities are certified according to the ISO 9001 and ISO 14001 management systems standards.

Sounds Beautiful

