

DATASHEET Rockfon® Soundstop



Sounds Beautiful

Rockfon® Soundstop

- Acoustic barriers which reduce noise transfer in ceiling and floor plenums
- Easy to install above or below modular partitions

Product Description

- Stone wool panel with aluminium foil membrane to one side
- 30 dB rating requires two layers of panels, each 30mm thick, placed back to back

Application Areas

- Office
- Healthcare
- s, Education
 - Industry
 - Leisure
 - Retail

| Edge detail | Module size (mm) | Weight (kg/m²) | A1-A3 Production stage impact (kg CO ₂ eq/m²)* | A1-C4 Full life cycle impact (kg CO₂ eq/m²)* |
|-----------------|---------------------|-------------------|---|--|
| Soundstop 21 dB | 1200 x 1000 x 65 | 4,7 | 5,83 | 7,14 |
| Soundstop 30 dB | 1200 x 1000 x 60 | 6,9 | 7,85 | 9,74 |

Soundstop 30 dB: The actual thickness equals 2x30 mm

* For full environmental impact disclosure, see our product EPDs available on **rockfon.link/cee-epd**. Due to differences in calculation methods and scenario assumptions, environmental impact values are generally not directly comparable between manufacturers.



Performance



Direct sound insulation $R_w = 21 \text{ dB}$ $R_{w} = 3021 \text{ dB}$



Room to room sound insulation

*) Values obtained on the basis of theoretical analysis.

| Product | $D_{n,f,w}$ | D _{n,f,w} with Rockfon Soundstop 21 dB | D _{n,f,w} with Rockfon Soundstop 30 dB |
|-----------------------------|-------------|--|--|
| Rockfon Blanka A (20mm) | 26 | | |
| Rockfon Blanka D/Aex (20mm) | 25 | | |
| Rockfon Blanka dB 35 | 35 | 44* | 50* |
| Rockfon Blanka dB 41 | 41 | 50* | 55* |
| Rockfon Blanka dB 43 | 43 | 53* | 56* |
| Rockfon Blanka dB 46 | 46 | 55* | 58* |
| Rockfon Sonar dB 35 | 35 | 44* | 50* |
| Rockfon Sonar dB 41 | 41 | 51* | 55* |
| Rockfon Sonar dB 43 | 43 | 52* | 56* |
| Rockfon Sonar dB 46 | 46 | 55* | 58* |



Reaction to fire C-s1,d0

(21 dB)

A1 (30 dB)



Humidity and sag resistance Up to 100% RH



Hygiene Stone wool provides no sustenance to microorganisms



Recyclability

Fully recyclable stone wool



لل

Indoor environment

Rockfon ceiling products are classified in Class E1 in accordance with EN 13964 (EN 717-1). Rockfon ceiling products have a very low release of VOCs. A selection of Rockfon products have achieved the following performance levels and labels in indoor air emissions:





Material Health

All materials used in Rockfon products are screened against the list of substances restricted under REACH and do not contain substances of very high concern (SVHC). Rockfon stone wool fibres comply with the safe fibre EU regulation and hold an EUCEB certification.

Sounds Beautiful

